

INSTRUCCIONES DE USO DE LAS MEDIAS MÁSCARAS FILTRANTES

Nombre del producto: media máscara filtrante

Modelo: LYN900-N909

Estándar de referencia: EN 149:2001+A1:2009 FFP2 NR

Fecha del producto / tiempo de caducidad: consulta la información en el embalaje de la caja

Reglamento (UE) 2016/426 de el Parlamento Europeo y del Consejo (09/03/2016)

Uso previsto de medias máscaras:

La semi máscara filtrante es un equipo completo de protección respiratoria y está destinada para proteger al usuario contra los efectos nocivos de la contaminación del aire en forma de sólidos y/o partículas líquidas que forman aerosoles (polvos, humos y nieblas)

Inspección antes del uso:

Antes de cada uso, verifique la fecha de almacenamiento de una media máscara y el estado técnico; si la media máscara no tiene daños mecánicos visibles, no está contaminada o incompleta. Una media máscara dañada y aquella cuyos datos de almacenamiento se han excedido no puede ser usada.

Condiciones de uso, restricciones de uso, contraindicaciones:

- Antes de usar una media máscara, lea las instrucciones de uso
- El usuario debe estar familiarizado con el equipo, su finalidad y las reglas de uso.
- Antes de usar una media máscara, el tipo y la concentración de aerosoles en el lugar de trabajo se debe conocer
- Uso de medias máscaras en una atmósfera contaminada con partículas de aerosol en una concentración superior al rango dedicado para clases de filtrado individuales según a la tabla siguiente – el riesgo de intoxicación
- Usar en una atmósfera, donde ocurre un fenómeno de deficiencia de oxígeno (concentración de oxígeno por debajo del 17% de volumen) – habitaciones con baja ventilación, espacio reducido, pasajes estrechos, canales, pozos de inspección, tanques, cisternas, silos; en caso de deficiencia de oxígeno, únicamente Utilice equipo de protección respiratoria aislante (ej: respiración de aire comprimido, aparato de regeneración) – posibilidad de desmayo, disnea.
- Uso en una atmósfera en la que se produzcan impurezas en forma de sustancias inorgánicas y/o vapores de sustancias orgánicas – riesgo de intoxicación.
- Modificación de la sujeción de las cintas para la cabeza y el método de ajuste en una manera inconsistente con las recomendaciones del fabricante – el riesgo de falta de ajuste y protección
- Modificación de los elementos del sellado, la pinza nasal, la esponja de sellado – el riesgo de falta de ajuste y protección
- Sellado de la válvula respiratoria (se refiere a las semi máscaras con válvulas respiratorias) Por riesgo de excesiva resistencia a la expiración (falta de conformidad de uso)

- Usar medias máscaras con otros tipos de equipo de protección personal (ojos, cabeza y protección auditiva) sin comprobar la ausencia de colisiones – el riesgo de falta de ajuste y protección
- Usar medias máscaras con daños mecánicos visibles (agujeros en el material, distorsiones) contaminado, incompleto - riesgo de falta de ajuste y protección
- Usar medias máscaras después de la fecha de caducidad - riesgo de falta de protección
- Almacenamiento y transporte de una manera y en condiciones distintas a las especificadas y recomendado por el fabricante – riesgo de perder las propiedades protectoras diseñadas
- Selección inadecuada de equipos para las amenazas predominantes – la falta de formación – riesgo de intoxicación
- El uso de medias máscaras a una temperatura demasiado alta de +50°C, o demasiado baja, de 30°C – riesgo de perder las propiedades protectoras diseñadas
- Usar medias máscaras en condiciones de humedad del aire superior al 80% - riesgo de perder las propiedades protectoras diseñadas
- Uso de semi máscaras marcadas con las letras NR para más de un turno de trabajo – riesgo de desprotección
- Reutilización de medias máscaras marcadas con las letras NR después de haber sido utilizadas por un turno de trabajo
- Usar medias máscaras marcadas con la letra R para mas de 3 turnos de trabajo recomendado por el fabricante – riesgo de falta de protección

Contraindicaciones:

- Usar medias máscaras en una atmósfera de deficiencia de oxígeno
- Usar medias máscaras en una atmósfera contaminada con partículas arriba dedicadas. Rangos e concentración de NDS para clases de filtrado individuales
- Uso de medias máscaras en forma de gases y vapores
- Uso indebido de medias máscaras
- El uso de medias máscaras marcadas con NR para mas de un turno de trabajo.
- El uso de medias máscaras a una temperatura demasiado alta de +50°C, o demasiado baja, de 30°C
- Usar medias máscaras en condiciones de humedad del aire superior al 80%
- Usar medias máscaras con daños mecánicos visibles
- Usar medias máscaras con riesgo de excesiva resistencia a la expiración
- Usar medias máscaras después de la fecha de caducidad
- Modificar elementos que constituyen componentes de las medias macaras
- El uso de las máscaras con vello facial causara problemas de fugas, si no cubre todo el vello facial, es poco probable que logre el sellado.

Almacenamiento, mantenimiento y transporte

- Las medias máscaras deben almacenarse en un embalaje cerrado y sin daños. Plásticos, bolsas yo cajas de cartón en habitaciones con humedad relativa inferior al 80% y temperatura de -30°C+50°C
- El tiempo máximo de almacenamiento en las condiciones requeridas es de 12 meses.
- Las medias máscaras deben protegerse de la luz solar directa, el calor y los productos químicos agresivos. Sustancias, humedad, suciedad y daños mecánicos.

FFP2: símbolos de la carcasa protectora de la semi máscara filtrante (nivel de protección de acuerdo con EN 149:2001+A1:2009)

NR: abreviatura de una letra que identifica la restricción de uso a un máximo de un turno (no reutilizable)

EN 149:2001 o EN 149:2001+a1:2009 – el numero y el año de la publicación del estándar de referencia

La declaración de conformidad se debe entregar con la mercancía.

INFORMACIÓN DE FABRICACIÓN

Código de la fabricación 91330326726586004L

ZHEJIANG LUYAO ELECTRONICS TECHNOLOGY CO., LTD

Wei 1st Road, Mechanical Park, Wanquan Light Industrial Base PingYang County, WenZhou City, Zhejiang Province, China

Cuerpo notificado:

Universal Certification and Surveillance Service Trade Ltd. Co.

Necip Fazıl Bulvarı Keyap Sitesi E2 Blok No: 44/84 Yukarı Dudullu Ümraniye-Istanbul
Country : Turkey

Phone : +90 216 455 80 80

Fax : +90 216 455 80 08

Email : info@universalcert.com

Website : www.universalcert.com

Notified Body number : 2163

MASCARILLA FFP2 RINMASK

46*78mm

合格证

产品名称: 非医用口罩

产品型号: LY-N900-N909

规格: 15.5*10.5 cm

材料: 面层:100%聚酯纤维

中间层:100%ES纤维

过滤层1:100%PTFE

过滤层2:100%聚丙烯

里层:100%聚酯纤维

执行标准: EN149:2001+A1:2009 FFP2 NR

过滤等级: FFP2

生产批号: 202012

生产日期: 2020/12

有效期: 24个月

原产地: 中国

储存条件: -30°C < 温度 < 50°C 湿度 < 80%

生产厂家: 浙江璐瑶电子科技有限公司

生产地址: 浙江省平阳县万全轻工基地机械园纬一路

产品使用范围: 本产品不得用于发热门诊隔离病房(区), 隔离留观病房(区), 手术室, 隔离重症监护等区域。



CERTIFICADO DE CONFORMIDAD

Nombre del producto: Máscara Protectora

Autofiltrante FFP2 RINMASK (Filtering half mask)

Modelo: LY-N900-N909

Tamaño: 15.5 X 10.5 cm

Material: 1ª Capa (Superficie): 100% Fibra Poliéster

2ª Capa: 100% Fibra ES

3ª Capa: 100% PTFE

4ª Capa: 100% Polipropileno

5ª Capa: 100% Fibra Poliéster

Estándar: EN 149:2001+A1:2009 FFP2 NR

Grado Filtro: FFP2

Lote producción: 202012

Fecha producción: 2020/12

Validez: 24 meses

Origen: China

Especificaciones de almacenamiento: -30°C <

Temperatura < 50°C Humedad < 80%

ZHEJIANG LUYAO ELECTRONICS TECHNOLOGY CO.,LTD

Wei 1st Road,Mechanical Park,Wanquan Light Industrial Base

PingYang County,WenZhou City,ZheJiang Province,China

Uso: Este producto no puede ser usado en salas de aislamiento, salas de observación, quirófanos, o salas de cuidado intensivo.

NO ES PRODUCTO SANITARIO





NB 2163

EU TYPE EXAMINATION CERTIFICATE

Certificate No: 2163 - PPE-730

Respiratory protective devices, filtering half masks to protect against particles manufactured by
Zhejiang Luyao Electronics Technology Co., Ltd.
Wei 1st Road Mechanical Park, Wanquan Light Industrial Base Pingyang, Wenzhou, Zhejiang,
China

are tested and evaluated according to

**EN 149:2001 + A1:2009 Respiratory Protective Devices -
Filtering Half Masks to Protect Against Particles -
Requirements, Testing, Marking**

Based on the type examination conducted with the evaluation of test reports, technical file according to Personal Protective Equipment Regulation (EU) 2016/425 Annex 5, it is approved that the product meets the requirements of the regulation.

Product Definition**Brand Name:** LUYAO **Model:** LY-N900-N909

Filtering half mask

Classification: FFP2 NR

Here by the manufacturer is allowed to use notified body number (2163) and can fix CE mark, as shown below, on the Category III product models given above, with;

- Issuing an appropriate EU Declaration of Conformity according to **Personal Protective Equipment Regulation (EU) 2016/425 Annex 9.**
- Ongoing successful performance in fulfilment of the requirements set out in Personal Protective Equipment Regulation (EU) 2016/425 and harmonised standards, ensured by assessments based on **Annex 7 (Module C2) or Annex 8 (Module D)** of the regulation no later than 1 year from the beginning of serial production

This certificate is initially issued on **09 /06/2020** and will be valid for 5 years, if there is no change in the relevant harmonised standard affecting the essential health and safety requirements.



Suat KACMAZ
UNIVERSAL CERTIFICATION
Director

CERTIFICATE OF CONFORMANCE

Certificate No: 2163 - PPE – 730/01

Respiratory protective devices, filtering half masks to protect against particles manufactured by

Zhejiang Luyao Electronics Technology Co., Ltd.

Wei 1st Road Mechanical Park, Wanquan Light Industrial Base Pingyang, Wenzhou, Zhejiang,
CHINA

Continues to fulfil the requirements of

**EN 149:2001 + A1:2009 Respiratory Protective Devices -
Filtering Half Masks to Protect Against Particles -
Requirements, Testing, Marking**

Based on the evaluation of test reports and internal quality control audit reports according to EN 149+A1:2009 and Personal Protective Equipment Regulation (EU) 2016/425 Annex VII (Module C2). This certificate implies that the manufactured products show below are in conformance with the approved EU Type Examination model and meets the requirements of the regulation.

Product Definition


Model	Class	EU Type Examination Certificate		
		Serial No	Date	Issuing NB No
LUYAO / LY-N900-N909	FFP2 NR	2163-PPE -730	09.06.2020	2163

Here by the manufacturer is allowed to use notified body number (2163) and can fix CE mark, as shown below, on the Category III product models given above, with;

- Issuing an appropriate EU Declaration of Conformity according to **Personal Protective Equipment Regulation (EU) 2016/425 Annex 9**.
- Taking all measures necessary so that the manufacturing process and its monitoring ensure the homogeneity of production and conformity of the manufactured PPE with the type described in the EU type examination certificate.

This certificate is issued on **09/06/2020** and will be valid for one year, until **08/06/2021** if the manufacturer makes no major change in the product designs and manufacturing processes affecting the product performance on the essential health and safety requirement.




Suat KACMAZ
UNIVERSAL CERTIFICATION
Director



TECHNICAL ASSESSMENT REPORT

REPORT DATE / NO: 09.06.2020 / 2163-KKD-730

Manufacturer: Zhejiang Luyao Electronic Technology Co., Ltd.

Address: Wei 1st Road Mechanical Park, Wanquan Light Industrial Base Pingyang, Wenzhou, Zhejiang, China

This report is for the, given above, manufacturer prepared according to the test results obtained from BEFITLAB Test Technology Shanghai Co., Ltd. accredited by IAS (International Accreditation Service), signatory to ILAC MRA, with number TL-787 for the product identified below, dated 30.05.2020 with Serial Id BT20200669T based on EN 149: 2001 + A1: 2009 standard and the technical file dated 31 May 2020 Version 01 provided by the manufacturer. The sampling of the product is conducted under our supervision for testing from the manufacturing site of the client.

The technical file of the manufacturer, and risk evaluation against the essential health safety requirements and the test report evaluated for their relation with Essential Requirements of Personal Protective Equipment Regulation and found to be appropriate.

This report is an annex and an integral part of the EU Type Examination Certificate issued to the manufacturer. The test results and issued certificate belongs only to the tested model. The technical report consists of a total of 6 pages.

Product Description: Particle Filtering Half Mask

Classification: FFP2 NR

Trademark: LUYAO **Model:** LY-N900-N909



**THE CLAUSES OF EN 149: 2001 + A1: 2009 STANDARD RELATED TO EUROPEAN UNION DIRECTIVE
EU 2016/425 REQUIREMENTS**

1.1. Design principles

1.1.1. Ergonomics

PPE must be so designed and manufactured that in the foreseeable conditions of use for which it is intended the user can perform the risk related activity normally whilst enjoying appropriate protection of the highest possible level.

1.1.2. Levels and classes of protection

1.1.2.1. Highest level of protection possible

The optimum level of protection to be taken into account in the design is that beyond which the constraints by the wearing of the PPE would prevent its effective use during the period of exposure to the risk or normal performance of the activity.

1.1.2.2. Classes of protection appropriate to different levels of risk

Where differing foreseeable conditions of use are such that several levels of the same risk can be distinguished, appropriate classes of protection must be taken into account in the design of the PPE.

1.2. Innocuousness of PPE

1.2.1. Absence of risks and other inherent nuisance factors

PPE must be so designed and manufactured as to preclude risks and other nuisance factors under foreseeable conditions of use.

1.2.1.1. Suitable constituent materials

The materials of which the PPE is made, including any of their possible decomposition products, must not adversely affect the health or safety of users.

1.2.1.2. Satisfactory surface condition of all PPE parts in contact with the user

Any part of the PPE that is in contact or is liable to come into contact with the user when the PPE is worn must be free of rough surfaces, sharp edges, sharp points and the like which could cause excessive irritation or injuries

1.2.1.3. Maximum permissible user impediment

Any impediment caused by PPE to movements to be made, postures to be adopted and sensory perception must be minimized; nor must PPE cause movements which endanger the user or other persons.

1.3 Comfort and effectiveness

1.3.1. Adaptation of PPE to user morphology

PPE must be designed and manufactured in such a way as to facilitate its correct positioning on the user and to remain in place for the foreseeable period of use, bearing in mind ambient factors, the actions to be carried out and the postures to be adopted. For this purpose, it must be possible to adapt the PPE to fit the morphology of the user by all appropriate means, such as adequate adjustment and attachment systems or the provision of an adequate range of sizes.

1.3.2. Lightness and design strength

PPE must be as light as possible without prejudicing design strength and efficiency.

Apart from the specific additional requirements which they must satisfy in order to provide adequate protection against the risks in question (see 3), PPE must be capable of withstanding the effects of ambient phenomena inherent under the foreseeable conditions of use

1.4. Information supplied by the manufacturer

The notes that must be drawn up by the former and supplied when PPE is placed on the market must contain all relevant information on:

- a) In addition to the name and address of the manufacturer and/or his authorized representative established in the Community
- b) Storage, use, cleaning, maintenance, servicing and disinfection. cleaning, maintenance or disinfectant protection recommended by manufacturers must have no adverse effect on PPE or users when applied in accordance with the relevant instructions;
- c) Performance as recorded during technical tests to check the levels or classes of protection provided by the PPE in question;
- d) Suitable PPE accessories and the characteristics of appropriate spare parts;
- e) The classes of protection appropriate to different levels of risk and the corresponding limits of use;
- f) The obsolescence deadline or period of obsolescence of PPE or certain of its components;
- g) The type of packaging suitable for transport;
- h) The significance of any markings (see 2.12)
- i) Where appropriate the references of the Directives applied in accordance with Article 5(6) (b);
- j) The name, address and identification number of the notified body involved in the design stage of the PPE

These notes, which must be precise and comprehensible, must be provided at least in the official language(s) of the member state of destination

2. ADDITIONAL REQUIREMENTS COMMON TO SEVERAL CLASSES OR TYPES OF PPE

2.1. PPE incorporating adjustment systems

If PPE incorporates adjustment systems, the latter must be designed and manufactured so that, after adjustment, they do not become undone unintentionally in the foreseeable conditions of use.

2.3. PPE for the face, eyes and respiratory system

Any restriction of the user's face, eyes, field of vision or respiratory system by the PPE shall be minimised.

The screens for those types of PPE must have a degree of optical neutrality that is compatible with the degree of precision and the duration of the activities of the user.

If necessary, such PPE must be treated or provided with means to prevent misting-up.

Models of PPE intended for users requiring sight correction must be compatible with the wearing of spectacles or contact lenses.

2.4. PPE subject to ageing

If it is known that the design performance of new PPE may be significantly affected by ageing, the month and year of manufacture and/or, if possible, the month and year of obsolescence must be indelibly and unambiguously marked on each item of PPE placed on the market and on its packaging.

If the manufacturer is unable to give an undertaking with regard to the useful life of the PPE, his instructions must provide all the information necessary to enable the purchaser or user to establish a reasonable obsolescence month and year, taking into account the quality level of the model and the effective conditions of storage, use, cleaning, servicing and maintenance.

Where appreciable and rapid deterioration in PPE performance is likely to be caused by ageing resulting from the periodic use of a cleaning process recommended by the manufacturer, the latter must, if possible, affix a marking to each item of PPE placed on the market indicating the maximum number of cleaning operations that may be carried out before the equipment needs to be inspected or discarded. Where such a marking is not affixed, the manufacturer must give that information in his instructions.

2.6. PPE for use in potentially explosive atmospheres

PPE intended for use in potentially explosive atmospheres must be designed and manufactured in such a way that it cannot be the source of an electric, electrostatic or impact-induced arc or spark likely to cause an explosive mixture to ignite.

2.8. PPE for intervention in very dangerous situations

The instructions supplied by the manufacturer with PPE for intervention in very dangerous situations must include, in particular, data intended for competent, trained persons who are qualified to interpret them and ensure their application by the user.

The instructions must also describe the procedure to be adopted in order to verify that PPE is correctly adjusted and functional when worn by the user.

Where PPE incorporates an alarm which is activated in the absence of the level of protection normally provided, the alarm must be designed and placed so that it can be perceived by the user in the foreseeable conditions of use.

2.9. PPE incorporating components which can be adjusted or removed by the user

Where PPE incorporates components which can be attached, adjusted or removed by the user for replacement purposes, such components must be designed and manufactured so that they can be easily attached, adjusted and removed without tools.

2.12. PPE bearing one or more identification or recognition marks directly or indirectly relating to health and safety

The identification or recognition marks directly or indirectly relating to health and safety affixed to these types or classes of must preferably take the form of harmonized pictograms or ideograms and must remain perfectly legible throughout the foreseeable useful life of the PPE. In addition, these marks must be complete, precise and comprehensible so as to prevent any misinterpretation; in particular, where such marks incorporate words or sentences, the latter must appear in the official language(s) of the Member State where the equipment is to be used.

If PPE (or a PPE component) is too small to allow all or part of the necessary marking to be affixed, the relevant information must be mentioned on the packing and in the manufacturer's notes.

3. ADDITIONAL REQUIREMENTS SPECIFIC TO PARTICULAR RISKS

3.10.2. Protection against cutaneous and ocular contact

PPE intended to prevent the surface contact of all or part of the body with substances and mixtures which are hazardous to health or with harmful biological agents must be capable of preventing the penetration or permeation of such substances and mixtures and agents through the protective integument under the foreseeable conditions of use for which the PPE is intended.

To this end, the constituent materials and other components of those types of PPE must be chosen or designed and incorporated so as to ensure, as far as possible, complete leak-tightness, which will allow where necessary prolonged daily use or, failing this, limited leak-tightness necessitating a restriction of the period of wear.

Where, by virtue of their nature and the foreseeable conditions of their use, certain substances and mixtures which are hazardous to health or harmful biological agents possess high penetrative power which limits the duration of the protection provided by the PPE in question, the latter must be subjected to standard tests with a view to their classification on the basis of their performance. PPE which is considered to be in conformity with the test specifications must bear a marking indicating, in particular, the names or, in the absence of the names, the codes of the substances used in the tests and the corresponding standard period of protection. The manufacturer's instructions must also contain, in particular, an explanation of the codes (if necessary), a detailed description of the standard tests and all appropriate information for the determination of the maximum permissible period of wear under the different foreseeable conditions of use.




Technical Assessment of EN 149: 2001 + A1: 2009 Standard and other Standards it refers to, Clauses Corresponding to the
(EU) 2016/425 Directive

Conforming to EN 149:2001 + A1:2009 Standard Requirements

Article 5	<p>Classification: Particle Filtering Half Mask</p> <p>The mask subject to evaluation based on the test results and technical file provided by the manufacturer is classified as; Filtering Efficiency and maximum Total Inward Leakage: Classified as FFP2</p> <p>Mask is classified for single shift use, NR</p>																																				
Article 7.4	<p>Packing: Particle filtering half masks are packaged to protect them from contamination before use and with cardboard boxes to prevent mechanical damage. The packaging design and the product is considered to withstand the foreseeable conditions of use based on the visual inspection results given in the test report.</p>																																				
Article 7.5	<p>Material: Materials used in particle filtering half masks, according to the simulated wearing treatment and temperature conditioning results; It is understood it withstands handling and wear over the period for which the particle filtering half mask is designed to be used, it suffered mechanical failure of the facepiece or straps, any material from the filter media released by the air flow through the filter has not constitute a hazard or nuisance for the wearer. The manufacturer declares that the materials used in manufacturing of the mask does not have an adverse affect to the health and safety of users.</p> <p>Based on the test results, the masks did not collapse when subject to simulated wearing and temarature conditioning. No nuisance situation is reported during the practical performance tests by human subjects.</p>																																				
Article 7.6	<p>Cleaning and Disinfection: Particle filtering half mask is not designed to be as re-usable. No cleaning or disinfection procedure provided by the manufacturer.</p>																																				
Article 7.7	<p>Practical Performance :</p> <p>The test report indicates that the human subjects did not face any difficulty in performing the excercises while they were weared by the sample masks, in walking test or work simulation tests. The wearers did not report any failure by means of head harness / straps/ earloops comfort, security of fastenings and field of vision. Also no imperfections reported during total inward tests about the comfort, field of vision and fastening issues.</p> <table><tr><th>Assessed Elements</th><th>Positive</th><th>Negative</th><th>Requirements in accordance with EN 149:2001 + A1:2009 and Result</th></tr><tr><td>2.Head harness comfort</td><td>2</td><td>0</td><td rowspan="3">Positive results are obtained from the test subjects No imperfections</td></tr><tr><td>3.Security of fastenings</td><td>2</td><td>0</td></tr><tr><td>5.Field of vision</td><td>2</td><td>0</td></tr></table> <p>Conditioning : (A.R.) As Received, original</p>	Assessed Elements	Positive	Negative	Requirements in accordance with EN 149:2001 + A1:2009 and Result	2.Head harness comfort	2	0	Positive results are obtained from the test subjects No imperfections	3.Security of fastenings	2	0	5.Field of vision	2	0																						
Assessed Elements	Positive	Negative	Requirements in accordance with EN 149:2001 + A1:2009 and Result																																		
2.Head harness comfort	2	0	Positive results are obtained from the test subjects No imperfections																																		
3.Security of fastenings	2	0																																			
5.Field of vision	2	0																																			
Article 7.8	<p>Finish of Parts: The test report states that the particle filtering half masks, which are likely to come into contact with the user, do not have sharp edges and do not contain burrs.</p>																																				
Article 7.9.1	<p>Total Inward Leakage:</p> <p>The Total Inward Lekage test is conducted by 10 individual in an aerosol chamber with a walking band, and samples are taken during the conduction of the excercises defined in the standard. The samples used in the test are subjected to the conditioning required in the standard as Temperature conditioning and as received. The face dimensions of the subjects are also reported. The measurement details for each subject and for each excersize are available in the test report.</p> <p>It was reported that;</p> <p>All 50 exercise measurement results are smaller or equal to 11% the values varies between 5,0 % and 9,9 %.</p> <p>All 10 individual's arithmetic mean is smaller or equal to 8% the values varies between 6,9 % and 7,9 %.</p> <p style="text-align: center;">According to the reported results, the product meets the limits for FFP1 and FFP2 classification.</p>																																				
Article 7.9.2	<p>Penetration of filter material: Sodium Chloride Testing</p> <table><tr><th>Condition</th><th>No. of Sample</th><th>Sodium Chloride Testing 95 L/min max (%)</th><th>Requirements in accordance with EN 149:2001 + A1:2009</th><th>Result</th></tr><tr><td>(A.R.)</td><td>11</td><td>2,3</td><td rowspan="3">FFP1 ≤ 20 %</td><td rowspan="9">Filtering half masks fulfill the requirements of the standard EN EN 149:2001 + A1:2009 given in 7.9.2 in range of the FFP1, FFP2 classes.</td></tr><tr><td>(A.R.)</td><td>12</td><td>1,3</td></tr><tr><td>(A.R.)</td><td>13</td><td>0,5</td></tr><tr><td>(S.W.)</td><td>14</td><td>1,7</td><td rowspan="3">FFP2 ≤ 6 %</td></tr><tr><td>(S.W.)</td><td>15</td><td>2,5</td></tr><tr><td>(S.W.)</td><td>16</td><td>1,4</td></tr><tr><td>(M.S. T.C.)</td><td>17</td><td>1,8</td><td rowspan="3">FFP3 ≤ 1 %</td></tr><tr><td>(M.S. T.C.)</td><td>18</td><td>1,8</td></tr><tr><td>(M.S. T.C.)</td><td>19</td><td>1,6</td></tr></table> <p>Conditioning : (M.S.) Mechanical Strength (T.C.) Temperature Conditioning (A.R.) As Received, original (S.W.) Simulated wearing treatment</p> <p style="text-align: right;">95 L/min = 1,6 dm³.sn⁻¹</p>	Condition	No. of Sample	Sodium Chloride Testing 95 L/min max (%)	Requirements in accordance with EN 149:2001 + A1:2009	Result	(A.R.)	11	2,3	FFP1 ≤ 20 %	Filtering half masks fulfill the requirements of the standard EN EN 149:2001 + A1:2009 given in 7.9.2 in range of the FFP1, FFP2 classes.	(A.R.)	12	1,3	(A.R.)	13	0,5	(S.W.)	14	1,7	FFP2 ≤ 6 %	(S.W.)	15	2,5	(S.W.)	16	1,4	(M.S. T.C.)	17	1,8	FFP3 ≤ 1 %	(M.S. T.C.)	18	1,8	(M.S. T.C.)	19	1,6
Condition	No. of Sample	Sodium Chloride Testing 95 L/min max (%)	Requirements in accordance with EN 149:2001 + A1:2009	Result																																	
(A.R.)	11	2,3	FFP1 ≤ 20 %	Filtering half masks fulfill the requirements of the standard EN EN 149:2001 + A1:2009 given in 7.9.2 in range of the FFP1, FFP2 classes.																																	
(A.R.)	12	1,3																																			
(A.R.)	13	0,5																																			
(S.W.)	14	1,7	FFP2 ≤ 6 %																																		
(S.W.)	15	2,5																																			
(S.W.)	16	1,4																																			
(M.S. T.C.)	17	1,8	FFP3 ≤ 1 %																																		
(M.S. T.C.)	18	1,8																																			
(M.S. T.C.)	19	1,6																																			

Article 7.9.2	Penetration of filter material: : Paraffin Oil Testing					
	Condition	No. of Sample	Paraffin Oil Testing 95 L/min max (%)	Requirements in accordance with EN 149:2001 + A1:2009	Result	
	(A.R.)	20	1,7	FFP1 ≤ 20 %	Filtering half masks fulfill the requirements of the standard EN EN 149:2001 + A1:2009 given in 7.9.2 in range of the FFP1, FFP2 classes.	
	(A.R.)	21	2,7			
	(A.R.)	22	2,2			
	(S.W.)	23	2,0	FFP2 ≤ 6 %		
	(S.W.)	24	1,9			
	(S.W.)	25	3,1			
	(M.S. T.C.)	26	2,9	FFP3 ≤ 1 %		
	(M.S. T.C.)	27	2,5			
	(M.S. T.C.)	28	2,0			
Conditioning : (M.S.) Mechanical Strength (T.C.) Temperature Conditioning (A.R.) As Received, original (S.W.) Simulated wearing treatment						
Article 7.10	Compatibility with skin: In Practical Performance report, the likelihood of mask materials in contact with the skin causing irritation or other adverse effect on health was not reported.					
Article 7.11	Flammability :					
	Condition	No. of Sample	Visual inspection	Requirements in accordance with EN 149:2001 + A1:2009	Result	
	(A.R.)	29	Burn for 0s	Filtering half mask shall not burn or not continue to burn for more than 5 s after removal from the flame	Passed Filtering half masks fulfill requirements of the standard	
	(A.R.)	30	Burn for 0s			
	(T.C.)	31	Burn for 0s			
	(T.C.)	32	Burn for 0s			
Conditioning : (A.R.) As Received, original (T.C.) Temperature Conditioning						
Article 7.12	Carbon dioxide content of the inhalation air:					
	Condition	No. of Sample	CO ₂ content of the inhalation air [%] by volume	An average CO ₂ content of the inhalation air	Requirements in accordance with EN 149:2001 + A1:2009	Result
	(A.R.)	33	0,69	0,69	CO ₂ content of the inhalation air shall not exceed an average of 1,0% by volume	Passed Filtering half masks fulfil requirements of the standard
	(A.R.)	34	0,68			
	(A.R.)	35	0,71			
	Conditioning : (A.R.) As Received, original					
Article 7.13	Head harness: In Practical Performance and TIL test reports no adverse effects have been reported for donning and remove of the mask also the results of these tests indicates that the ear loops / head harness are capable of holding the mask firmly enough.					
Article 7.14	Field of vision: In Practical Performance report, no adverse effects were reported for the field of vision availability when the mask is wearred.					
Article 7.15	Exhalation Valve(s): The model under inspection have no valves.					
Article 7.16	Breathing Resistance: Inhalation					
	The overall evaluation of the results gathered for 9 different samples 3 as received, 3 with temperature conditioning, 3 simulated wearing treatment complies with the limits given in the standard for FFP1, FFP2 and FFP3 classes. This is valid for inhalation results for 30 L/min, 95 L/min and exhalation at 160 L/min. The measurement details for each single mask tested are available in the test report. Passed.					

Article 7.17	Clogging: This test is not applied to Particle Filtering Half Mask which is not reusable. <i>(For single shift use devices, the clogging test is optional test. For re-usable devices test is mandatory.)</i>
Article 7.18	Demountable Parts: There are no demountable parts of the mask.
Article 8	Testing: All tests conducted according to Clause 8 of this standard is available in the test report and are evaluated in this report for qualification and classification of the mask.
Article 9	Marking – Packaging: Necessary markings are available on the product package (box). The manufacturer and its trademark is clearly visible. The type of the mask and the classification including the status of re-usability, the reference to EN 149:2001+A1:2009 standard, the end date of shelf life, using and storage instructions and pictograms and CE mark are available on the product package. The above evaluation is based on the technical document for packaging and marking, for box design. Verified on the Annex 9.1 of the technical file. The technical documentation for mask design (drawing) also evaluated for marking requirements, drawing LY-N900-N909. The mask template (drawing) indicates that the mask will carry information about the manufacturer / trademark (LUYAO) of the manufacturer, Type of mask, the reference to EN 149+A1:2009 standard and classification including the re-usability of the mask. The manufacturer also printed CE mark with our Notified Body number. The mask do not have sub-assemblies. Even the tested sample by the laboratory do not carry necessary marking information as stated in the technical documentation, the manufacturer shall follow marking instructions for serial production. Model drawing LY-N900-N909 exists in the technical file of the manufacturer, Annex 6 of technical file.
Article 10	Information to be supplied by the manufacturer: In each of the smallest commercially available packaging of the product, implementation (installation instructions) pre-use controls, warning and usage limitations, storage and meanings of symbols / pictograms are defined. User instruction document in the technical file found to be appropriate, Annex 8. The manufacturer shall include this documented user information text in every smallest commercially available package.

PREPARED BY	APPROVED BY
Osman CAMCI PPE Expert 	Suat KAÇMAZ General Manager  

EU Declaration of Conformity

Annex IX PPE Regulation (EU) 2016/425

This EU Declaration of conformity refers to the following products

Product Name	Model	Classification/Type	Batch No./Serial No./Identifier
Filtering half mask	LY-N900-N909	FFP2 NR	202101

The Manufacturer's name and address is as follows:

Name:	Zhejiang Luyao Electronics Technology Co.,Ltd
Address:	Wei 1st Road, Mechanical Park, Wanquan Light Industrial Base Pingyang, Wenzhou, Zhejiang, China

This Declaration of Conformity is issued under the sole responsibility of the Manufacturer.

Model: LY-N900-N909

White folder half mask without valve



Product Photo:

The article identified in product category is in conformance with the relevant Union Harmonization Legislation Regulation (EU) 2016/425.

References to the relevant harmonized standards used, including the date of the standard, or references to the other technical specifications, including the date of the specification, in relation to which conformity is declared:


No.	Harmonized standard name
1	EN 149:2001+A1:2009

Universal Certification and Surveillance Service Trade Ltd. Co. (NB 2163) performed the EU Type Examination (Module B) and issued the Type Examination Certificate Number:

No.	EU Type Examination (Module B) Certificate Number
1	2163-PPE-730

Product Category:

- ☐ This product is Category II.
- ☒ This product is Category III and is subject to Module C2 internal production control plus supervised product checks at random intervals and is under the surveillance of Universal Certification and Surveillance Service Trade Ltd. Co. (NB 2163)
- ☐ This product is Category III and is subject to Module D Conformity to type based on quality assurance of the production process and is under the surveillance of Universal Certification and Surveillance Service Trade Ltd. Co. (NB 2163)



Signature _____ Nom: YangPing Fonction Manager Date: 2021/01/19

